



SETUP

Faretto LED ad incasso per esterno, da terra, carrabile (max. 3500Kg a 30 Km/h); corpo in alluminio con vetro temperato e cassaforma in dotazione.

Ghiera e viti di fissaggio in acciaio INOX, guarnizioni in silicone per garantire un alto livello di protezione, IP67.

Alimentatore LED integrato. Disponibile in due temperature colore, 3000K e 4000K, con ottica simmetrica o asimmetrica.

Disponibili giunti certificati IP68 per la realizzazione delle connessioni elettriche, sicure, durevoli e con barriera anticondensa.

Drive over outdoor LED recessed luminaire, ground installation (max. 3500Kg at 30 Km/h). Aluminium body with tempered glass, recessed box included.

Stainless steel ring nut and fixing screws, silicone gasket to ensure a high protection grade, IP67.

Integrated LED driver. Available in two gradations, 3000K and 4000K, with symmetric or asymmetric optics.

IP68 linear connectors for moisture protection and anti-condensation linear joints are available.


OTTICA SIMMETRICA SYMMETRIC OPTICS




carrabile
max Kg 3500 - max 30Km/h
drive over
max Kg 3500 - max 30Km/h



Codice Code	CCT	Flusso lm Flux lm	Potenza Wattage	Dimensioni mm Dimensions mm
SET001	3000K	3800	23,3W	Ø245 x 330
SET002	4000K	3820	23,3W	Ø245 x 330



foro hole




OTTICA ASIMMETRICA ASYMMETRIC OPTICS




carrabile
max Kg 3500 - max 30Km/h
drive over
max Kg 3500 - max 30Km/h



Codice Code	CCT	Flusso lm Flux lm	Potenza Wattage	Dimensioni mm Dimensions mm
SET003	3000K	3800	23,3W	Ø245 x 330
SET004	4000K	3820	23,3W	Ø245 x 330



foro hole



Finiture Finishes



Acciaio satinato Satin steel

Accessori Accessories



connessione IP68
IP68 connection



Ottiche da 29° e 72°
disponibili su richiesta
29° and 72° optics
available on request



cassaforma
inclusa
recessed box
included

p.945